

Steam Condenser

User Manual

Check that all parts are included in the package.
Assemble all parts according to picture shown to the right.
Remember that all TC fittings need a silicone gasket.

Assemble your water supply parts to the top inlet in order to supply the unit with cold water. Remember to use a garden hose or similar that can withstand the normal tap water pressure. Recommended fittings are either a TC34mm to garden connector or a TC34mm to hose barb. Remember to use a hose clamp. Additionally, we recommend using one or two TC34mm elbows to ensure the water hose connects on top without bending and reducing the flow of water.

Install a tube to the outlet hose barb on the steam condenser. Included in the kit is a 19mm hose barb adapter which fits perfectly with our standard 16x25mm silicone tube. As the steam condenser creates a vacuum to suck out the steam, it is important that the drain hose is not causing counterpressure. We recommend letting the condensed steam flow vertically to a bucket or a drain in the floor. If your floor drain is not close, use a second hose from the bucket to the floor drain.

Installing the steam condenser to the steam hat requires a 4" TC clamp fitting and gasket (not included).

The unit ships with a nozzle that supplies 1.1 liters of water per minute at 4 bar pressure. We also offer other nozzles that offers higher or lower flow depending on the water pressure where the system is used and other factors (sold separately).

Please note that you need much less power to keep the boil going with this device, and the risk of the wort boiling over is high when too much power is used, so make sure to take the necessary precautions



*Steam is sucked through the 4" fitting.
Condensation happens when the cold water sprays
the cold mist downwards.
The condensed steam will drain out the bottom.*

Included in the kit:

- TC 4" to TC 2" adapter (1 pcs)
- 20cm straight TC 2" pipe (2 pcs)
- TC 2" Tee (1 pcs)
- TC 2" Elbow (1 pcs)
- TC 2" 1/8" nozzle adapter with TC34mm input (1 pcs)
- TC 2" to 19mm hose barb adapter (1 pcs)
- TC 2" Clamp (6 pcs)
- TC 2" Gasket (6 pcs)
- 1/8" BSP-T nozzle, 30 degrees, 1.1 liters per minute @ 4 bar (1 pcs)
- Nozzle extension